

Demolition & sorting grabs

Multi purpose grabs for demolition, recycling, sorting and loading

- 1) Top plate for bolt on bracket.
- 2) Continuous 360° hydraulic rotation
- 3) 1 cylinder from S223 to S1102
Twin cylinders from S1402 to S6002.
Dash pot on S802/S1102/S1702
S2002/S2301.
- 4) HF treated pins.
- 5) Shells in wear resistant steel.
Vertical shells opening to the ground.
- 6) Reversible bolt on wear blades in 450 HB steel

Option :
Closed shells for ROC version.



L

L
Roc

A

B

C

D

E

H

V

F



	Kg	mm	mm	mm	mm	mm	mm	≈ mm	mm	liters	daN	bar	liters/mn	sec	bar	liters/mn	RPM	t
S 223	200	400	-	1090	770	760	760	100	350	78	1200	250	8/15	2/4	100	6/9	10/15	2,5/4.5
S 303	268	460	-	1180	850	845	840	145	395	106	1900	300	10/20	2/4	100	8/12	10/15	4/6
S 453	370	550	-	1290	950	910	910	150	440	146	2500	350	15/30	2/4	100	8/12	10/15	6/8
S 603	540	650	-	1490	1100	1020	1020	200	500	250	3300	350	20/40	2/4	100	10/15	10/15	7/10
S 802	725	800	800	1710	1235	895	1060	530	540	395	4000	350	30/65	2/4	140	14/20	10/15	11/15
S 1102	930	900	900	1840	1370	990	1090	520	580	470	5000	350	45/80	2/4	140	14/20	10/15	15/18
S 1402	1220	1010	1010	2000	1434	1046	1281	300/400	616	700	6200	350	55/110	2/4	140	14/20	10/15	18/21
S 1702	1500	1120	1120	2100	1460	1180	1375	505	625	820	6000	350	55/110	2/4	140	14/20	10/15	22/27
S 2002	1770	1140	1140	2200	1500	1180	1370	350/450	695	950	8300	350	90/140	2/4	140	24/35	10/15	25/32
S 2301	2100	1210	1210	2270	1624	1270	1422	450/550	674	1080	9300	350	100/160	2/4	140	28/40	10/15	28/37
S 3002	2850	1450	1030	2400	1650	1330	1500	480/580	620	1270	10300	350	130/260	2/4	140	35/45	10/15	38/60
S 6002	5600	1600	1600	3120	1960	1600	2310	500/650	900	2200	13400	350	200/400	2/4	140	40/60	10/15	60/90

Weight (± 3%) without top plate

S223 - S303 - S453 - S603

S802 - S1102 - S1402 - S1702 - S2002 - S2301 - S3002 - S6002

